

### **STANDARD**

EN 397 | 440V a.c. / -30°C / LD / MM EN 50365 (Class 0)

€ 2008 EA 8503

# EN 12492

for the following clauses only: 4.2.1 | Shock energy absorption capacity 4.2.2 | Penetration



## **MATERIAL**

**EXTERNAL SHELL:** HD Polypropylene

**INTERNAL SHELL:** HD Expanded Polystyrene

**HEADBAND:** Soft PA Nylon



TEMPERATURE OF USE -30°C / +50°C



**WEIGHT** 

460 g



SIZE

Universal-adjustable from 52 to 63 cm



WHE00112

201 221











**CATEGORY** 

**TECHNOLOGIES** 

- **ERGO FIT SYSTEM** Moves up and down and cradles back of neck for a secure fit.
- **2DRY LINER** Moisture-wicking fabric technology for all-day comfort.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **ADVANCED LITE CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- > RING TO HOOK Chinstrap loop that securely attaches helmet to a harness.
- **EARMUFF ATTACHMENT SLOTS** Designed with 30mm EURO slots for attaching earmuffs.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- > REPLACEABLE LAMP CLIPS 4 lamp attachment clips designed to be removable.
- > HI-VIZ DETAILS High visibility color shell, luminescent lamp clips and reflective adhesives.

YEARS

YEARS LIFE SPAN

## **DISCOVER MORE**



SCAN FOR COMPLETE COLLECTION









