

STANDARD

EN 12492



EN 397 | -30°C / LD / MM for the following clauses only:

5.1.1 | Top impacts

5.1.2 | Penetration

5.1.3 | Flame resistance



EXTERNAL SHELL: HD Polypropylene



INTERNAL SHELL:

Neopor® Ccycled® by BASF | EPS obtained from chemical recycling of plastic waste.

HEADBAND: Soft PA Nylon



TEMPERATURE OF USE

-30°C / +50°C



WEIGHT

460 g



Universal-adjustable from 52 to 63 cm





WHE00116

201 221



TECHNOLOGIES

- **ERGO FIT SYSTEM** Moves up and down and cradles back of neck for a secure fit.
- > 2DRY LINER Moisture-wicking fabric technology for all-day comfort.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **ADVANCED LITE CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- > VENTILATION CHANNELS 14 air intakes that enhance breathability and comfort.
- > RING TO HOOK Chinstrap loop that securely attaches helmet to a harness.
- **EARMUFF ATTACHMENT SLOTS** Designed with 30mm EURO slots for attaching earmuffs.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- > REPLACEABLE LAMP CLIPS 4 lamp attachment clips designed to be removable.
- **HI-VIZ DETAILS** High visibility color shell, luminescent lamp clips and reflective adhesives.

10 YEARS











