## ΚΛ/Κ

ΕN

## **PERFORMANCE** WITH A MULTIPLIER EFFECT.

# ZENITH X LC HI VIZ



**STANDARD** EN 397 | 440V a.c. / -30°C / LD / MM EN 50365 (Class 0)

CE 2008 24 8503

### EN 12492

for the following clauses only: Shock energy absorption capacity 4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact 4.2.2 | Penetration



### **TECHNOLOGIES**

- > D-CORE TECHNOLOGY Low density inner core protects from top impacts.
- > HD CROWN PROTECTION High-density inner shell protection designed for all-around impacts.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- > DRY+ LINER Moisture-wicking fabric for enhanced comfort.
- **ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- > ADVANCED CHINSTRAP 5 adjustment points and EN color-coded fastener.
- > COLOR-CODED FASTENER The color of the fastener indicates the EN standard to which the chinstrap refers.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- > HI-VIZ DETAILS High visibility color shell, luminescent lamp clips and reflective adhesives.
- > LONGER CHINSTRAP Eco-leather chinstrap with 10 cm of added length for a personalized fit.





INTERNAL SHELL: • Neopor® Ccycled® by BASF | EPS • obtained from chemical recycling of plastic waste.

HEADBAND: Soft PA Nylon


#### **TEMPERATURE OF USE** -30°C / +50°C





Universal-adjustable from 52 to 63 cm

#### DESIGN AWARD 2021



3

YEARS

10

YEARS

FOR

SCAN

COMPLETE