

WAC00034-514

Flame and fire-resistant, full neck protection designed to also protect the wearer from heat and chemicals. Front hook-and-loop closure ensures secure protection of exposed skin and body parts.

Compatible with Zenith X, Zenith X2 and Primero helmets series.

## TECHNICAL DETAILS



### TEST

ASTM F1959/05 | IEC 61482/1  
ATPV 22.2 cal/cm<sup>2</sup>

### STANDARD

EN 13688 | Protective clothing - general requirements

EN 11612 | Heat and flame protection

A1 - Limited flame spread

B1 - Convective heat

C1 - Radiant heat

EN 13034 | Protection against chemicals

Type PB [6] - protection against liquid chemicals:

H2SO4 - 30% dilution

NaOH - 10% dilution

o-Xylene - undiluted

Butan-1-olo - undiluted

EN1149-5 | Electrostatic properties (base fabric only)

Half decay time t50 <4s

Shielding factor S >0.2s



## FIRE RESISTANT TECHNOLOGIES



### FIRE RESISTANT FABRIC

**Material:** Nomex® | Kevlar®

**Test:** ASTM F1959-05 | IEC 61482/1 | ATPV 22.2 cal/cm<sup>2</sup>

Fire-resistant Nomex® fabric. Non-melting, self-extinguishing with no flame.



### MATERIAL

Double layer fabric in 93% Nomex®, 5% Kevlar®,  
2% antistatic fiber



### WEIGHT

80.5 g | 0.17 lb

## TECHNOLOGIES



### NECK PROTECTION

Neck shade designed to protect wearer's neck from heat, flames and chemicals.



### EASY ATTACHMENT SYSTEM

Integrated slots that enable secure accessory attachment.



### PREVENTION

Anti-static base fabric prevents unexpected electrostatic buildup and discharge.



### HOOK AND LOOP FASTENER

Front hook-and-loop closure ensures secure protection of exposed skin and body parts.

## ADDITIONAL INFORMATION

### GUARANTEE

3 years from the date of purchase.

### CLEANING

The padding should be washed by hand in cold water (max 30°C - 85°F).

# 3

YEARS  
GUARANTEE

## DISCOVER MORE



SCAN FOR  
COMPLETE  
COLLECTION