WVI00034



Full face protection that enables the wearer to work on or be in the vicinity of live electric parts with Class 2 arc flash protection (GS-ET-29). Recommended for use with balaclava. Securely flips up and down. Attaches directly to the 30 mm EURO Slots.

Compatible with KASK Zenith X, Primero and Quantum helmet series.

# **TECHNICAL DETAILS**



#### **STANDARD**

EN ISO 16321-1 DGUV GS-ET-29 ANSI Z87.1 + ASTM F2178 CSA Z94.3

**GS-ET-29 (Box-Test)** 

Class 2 / APC 2

**C**€ 1883 **CA** 0843



### **CATEGORY** Ш



**MATERIAL** Polycarbonate







**WEIGHT** 



**LENGTH** 215 mm

# **TECHNOLOGIES**



#### **PANORAMIC LENS**

Developed to maximize visibility with minimal viewing distortion.



#### **COMPATIBLE WITH GLASSES**

Designed for use over corrective glasses.



## **STABLE CARRIER**

Reinforced face shield carrier for added protection and durability.



## **SEE-THROUGH CHIN PROTECTION**

Equipped with transparent chin protection for enhanced range of worksite visibility.



# > CRI 95

Designed with excellent Color Rendering Index performance for greater color contrast and visibility.

# **MARKINGS**

CODE	COLOR	MARKING
WV100034	SMOKE	KΛ/K
		CLASS 2 ERGO
		MM / YYYY 4 2 2 0 3 1
		<b>Ç€</b> 1883 <b>UK</b> 0843
		16321 KASK UL 2 E 6 9
		GS-ET-29 8-2-2 APC 2
		ATPV 12 cal/cm <sup>2</sup>
	:	ANSI / ISEA Z87.1
	:	KASK Z87+ U6
		CSA Z94.3
		KASK 2.0

# **ADDITIONAL INFORMATION**

### GUARANTEE

3 years starting from the date of purchase.

10 years starting from the date of manufacture. Life span depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor. YEARS

10 YEARS



COMPLETE COLLECTION









