



STANDARD

ANSI Z89.1 Type I, Class C HT-LT

EN 12492

for the following clauses only: Shock energy absorption capacity 4.2.1.2 front impact, 4.2.1.3 lateral impact,

4.2.1.4 rear impact

4.2.2 | Penetration

4.2.3 | Retention system strength

4.2.4 | Effectiveness of the retention system



MATERIAL

EXTERNAL SHELL: ABS



INTERNAL SHELL:

Neopor® Ccycled® by BASF | EPS obtained from chemical recycling of plastic waste.

HEADBAND: Soft PA Nylon



TEMPERATURE OF USE

-22°F / +140°F



WEIGHT

0.99 lb



224



SIZE

One size fits most

TECHNOLOGIES

- > 2DRY LINER Moisture-wicking fabric technology for all-day comfort.
- **) UP & DOWN SYSTEM** A size adjustment system that enables a comfort fit.
- > VENTILATION CHANNELS 10 air intakes that enhance breathability and comfort.
- **ANTI-INTRUSION MESH** Prevents debris from entering ventilation channels.
- **LATERAL ADJUSTMENT DIVIDER** Side adjustment points on chinstrap for secure fit.
- > DETACHABLE INNER PADDING Hook-and-loop-enabled padding for easy removal, replacement, & washing.
- > RING TO HOOK Chinstrap loop that securely attaches helmet to a harness.
- **EARMUFF ADAPTER ATTACHMENT POINTS** For adapters to secure earmuffs.
- **> VISOR ATTACHMENT POINTS** For securing KASK eye protection accessories.
- > INTEGRATED LUMINISCENT LAMP CLIPS 4 built-in, nylon lamp attachment points.
- > HI-VIZ DETAILS High visibility color shell, luminescent lamp clips and reflective adhesives.

10 YEARS

201 | 221 | 223











