



MATERIAL

EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

HEADBAND: Soft PA Nylon



SIZE

One size fits most



WEIGHT

430 g



STANDARD

CSA Z94.1 TYPE I - CLASS C EN 12492

Protection against side, front and rear impacts Shock energy absorption capacity (Clauses 4.2.1.2 - front, 4.2.1.3 - lateral, 4.2.1.4 - rear) Penetration (Clause 4.2.2) Retention system strength (Clause 4.2.3) Retention system effectiveness (Clause 4.2.4)



TEMPERATURE OF USE

-30°C / -50°C



WHE00124

201 221

DISCOVER MORE

TECHNOLOGIES

- **VENTILATION CHANNELS** 14 air intakes shaped for preventing debris entry.
- **ERGO FIT SYSTEM** Moves up and down and cradles back of neck for a secure fit.
- **2DRY LINER** Moisture-wicking fabric technology for all-day comfort.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **ADVANCED LITE CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- > RING TO HOOK Chinstrap loop that securely attaches helmet to a harness.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.
- **EARMUFF ATTACHMENT SLOTS** 30mm EURO slots for attaching earmuffs.
- **REPLACEABLE LAMP CLIPS** 4 removable nylon lamp attachment clips.
- HI VIZ DETAILS High visibility color shell, luminescent lamp clips and reflective decals.











SCAN FOR